

AIR OPERATED LOCKING DIFFERENTIAL

RD206

Suzuki Jimny,FR,22 SPL,10 Bolt RG

PARTS L	.IST			
ITEM#	QTY	DESCRIPTION	PART#	NOTES
01	1	FLANGE CAP KIT	028512SP	
02	1	BONDED SEAL	160701SP	
03	1	CLUTCH GEAR & WAVESPRING KIT	050908SP	
04	2	SHORT CROSS SHAFT	060309SP	
05	1	LONG CROSS SHAFT	060108SP	
06	1	SIDE GEAR	SEE NOTE	2
07	2	SIDE GEAR THRUST WASHER	SEE NOTE	3
08	1	COUNTERSUNK SCREW (PK OF 2)	200213SP	
09	1	RETAINING PIN SET (PK OF 4)	120601SP	
10	-	TAPERED ROLLER BEARING	NOT SUPPLIED	
11	1	SEAL HOUSING RETAINING CLIP	150603SP	
12	1	SEAL HOUSING KIT	081903SP	
13	1	SEAL HOUSING O-RINGS (PK OF 2)	160206-2	1
14	1	ADJUSTER NUT	100601SP	
15	1	WAVESPRING	150702SP	
16	1	SPLINED SIDE GEAR	SEE NOTE	2
17	4	PINION GEAR	SEE NOTE	2
18	4	PINION THRUST WASHER	SEE NOTE	3
19	1	SPIDER BLOCK	070702SP	
20	1	DIFFERENTIAL CASE	013112SP	
*	1	BULKHEAD FITTING KIT (BANJO TYPE)	170114	4
*	1	AIR LINE (6mm DIA X 6m LONG)	170314	4
*	1	SOLENOID VALVE (12V)	180103	
*	1	SWITCH FR LOCKER	180223	
*	1	CABLE TIE (PK OF 25)	180305	
*	1	OPERATING & SERVICE MANUAL	210200	
*	1	INSTALLATION GUIDE	2102206	

* Not illustrated in exploded view

NOTES

- 1 For replacement O-rings use only BS130 Viton 75.
- 2 Available only as complete 6 gear set # 728JA22
- 3 Available only as complete thrust washer kit #730JA01
- 4 All diffs produced before serial #17070001 came with 5mm air connection system. For information contact ARB.
- Refer to seal housing set-up tech note (Section 5.2).
- For 8 bolt ring gear model refer to RD207 (Section 2.207).





AIR OPERATED LOCKING DIFFERENTIAL

RD206

Suzuki Jimny,FR,22 SPL,10 Bolt RG

EXPLODED DIAGRAM 2 1 10 9 8 7 6 11 11 13 12 11 13 15

SPECIFICATIONS

Axle Spline 22 tooth, Ø23.9mm [0.94"]
Ratio Supported All

Ring Gear ID 108.0mm [4.25"]

Ring Gear Bolts 10 bolts on Ø130mm [5.12"] Ring Gear Torque 85Nm [63 ft-lb]

Backlash 0.10-0.20mm [0.004-0.008"]

Bearing Cap Torque 50Nm [37 ft-lb]

AIRLOCKER ARB